





● UF.10.NC120.NM



Dimension: mm NTS
High Power L.E.D

TECHNICAL DATA


Mode of Operation	: Non-Maintained
Lamp	: 10W High Power LED Module
Rated Duration	: 2 hr and others
Mains Supply	: 230 Volts, 50/60Hz
Power Consumption	: 5VA
Battery	: High temp nickel cadmium
Charge Monitor	: Green LED Ø5mm
Test Facility	: Micro switch
Safety Feature	: Low volt cut-off preventing battery overdischarge
Fitting Construction	: Electro galvanised steel with epoxy powder coating
Mounting	: Ceiling
Cable Entry	: Ø20mm K/O hole
Weight	: 1.5kg (gross)
Compliance	: SS 563 : Part 1 & 2, SS IEC 60598-2-22
Warranty	: 1 year

KEY FEATURES

- > High Brightness Output
- > High Lumen/watt Efficiency
- > Low Power Consumption
- > Low Maintenance
- > Long Lifespan
- > Mainly use for high ceiling (> 8 meters)

ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Model	Lamp	Battery type
UF.10.NC120.NM	10W LED Module	Nickel cadmium



Surface Mount
Emergency Luminaire

